



(19) SU⁽¹¹⁾ 1 798 383⁽¹³⁾ A1
(51) Int. Cl.

STATE COMMITTEE
FOR INVENTIONS AND DISCOVERIES

(12) ABSTRACT OF INVENTION

(71) Applicant:
KHARKOVSKIY GOSUDARSTVENNYJ
UNIVERSITET IM.A.M.GORKOGO

(72) Inventor: LARIN VASILIJ IVANOVICH,
GOROBETS SERGEJ
DMITRIEVICH, ABMANOVA NATALYA
ANDREEVNA

(54) METHOD OF REGENERATION OF SPENT ETCHING SOLUTION CONTAINING FERROUS AND FERRIC CHLORIDE AND COPPER

(57)
Сущность изобретения: восстановление травильной способности отработанного раствора, содержащего хлористое и хлорное железо и медь, осуществляют следующим образом. Проводят цементацию меди при избытке железного порошка до получения в растворе хлористого железа 4,3

моль/л, отделяют образовавшийся осадок железо-медь, а в раствор добавляют соляную кислоту до концентрации 1-2,48 моль/л, выкристаллизовывают осадок хлористого железа, отделяют этот осадок от раствора, а раствор подают на окисление для образования хлорного железа, 2 ил. 1 табл. (л)

SU 1 798 383 A1

SU 1 798 383 A1

File 351:Derwent WPI 1963-2005/UD,UM &UP=200524

(c) 2005 Thomson Derwent

*File 351: For more current information, include File 331 in your search.
Enter HELP NEWS 331 for details.

Set Items Description
--- -----

?

S PN=SU 1798383

S1 1 PN=SU 1798383

?

T1/9

1/9/1

DIALOG(R)File 351:Derwent WPI

(c) 2005 Thomson Derwent. All rts. reserv.

C09877731 **Image available**

WPI Acc No: 1994-157645/199419

XRAM Acc No: C94-072473

XRPX Acc No: N94-123846

Regenerating spent etching soln. contg. copper and ferrous and ferric chloride(s) - includes precipitating copper with excess iron@ powder

Patent Assignee: UNIV KHARK (UYKH)

Inventor: ABMANOVA N A; GOROBETS S D; LARIN V I

Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No	Kind	Date	Applicat No	Kind	Date	Week
SU 1798383	A1	19930228	SU 4879438	A	19901101	199419 B

Priority Applications (No Type Date): SU 4879438 A 19901101

Patent Details:

Patent No	Kind	Int. Pg	Main IPC	Filing Notes
SU 1798383	A1	4	C23G-001/36	

Abstract (Basic): SU 1798383 A

The solns. are regenerated by precipitating the Cu with an excess of Fe powder, sepg. the Fe-Cu residue formed and oxidising the ferrous chloride to the ferric state with Cl. In order to achieve the stated aims, the Cu is pptd. to produce a soln. contg. ferrous chloride at a 4.3 moles/litre concn. Before the said soln. is oxidised, the excess ferrous chloride is removed by adding HCl to produce a concn. of 1-2.48 moles/litre, the ferrous chloride is allowed to crystallise out and the said ferrous is sepd. by decanting.

Referring to the drawing, 1 is the both with the spent etching soln., 2 is the reactor for Cu pptn., 3 is a reactor for collecting the Fe-Cu residue, 4 is a reactor for crystallising out the ferrous chloride and 5 is the supply of conc. HCl.

USE/ADVANTAGE - Is used in the radio and electronics. The etching soln. balance is maintained before and after regeneration by avoiding the formation of excess ferric chloride.

Dwg.1/2

Title Terms: REGENERATE; SPENT; ETCH; SOLUTION; CONTAIN; COPPER; FERROUS; FERRIC; CHLORIDE; PRECIPITATION; COPPER; EXCESS; IRON; POWDER

Derwent Class: L03; M14; V04; X25

International Patent Class (Main): C23G-001/36

File Segment: CPI; EPI

Manual Codes (CPI/A-N): L03-H04E2; L03-H04E9; M14-A02

Manual Codes (EPI/S-X): V04-R01C1; V04-R15; X25-R06

Derwent Registry Numbers: 1704-U; 1939-P

?

COST

19apr05 02:04:21 User074199 Session D6718.2

\$8.92 0.284 DialUnits File351

\$6.11 1 Type(s) in Format 9

\$6.11 1 Types

\$15.03 Estimated cost File351

\$0.26 INTERNET

015.00 Estimated cost File351